

City of Seattle Department of Planning and Development

www.seattle.gov/dpd

SCREENING STANDARDS

Grading, Drainage and Stormwater INDEX 14

Applicant Services Center 700 Fifth Avenue, Suite 2000 P. O. Box 34019

Seattle, WA 98124-4019 **Phone:** (206) 684-8850

Hours: M/W/F, 7:30am-5:30pm; T/Th, 10:30am-5:30pm

You are responsible for verifying and accurately depicting all locations and dimensions of property lines; setback distances; and the location and width of streets, rights-of-way, easements and the City may require additional information as needed. If you have any questions concerning your application submittal, please visit or call the Applicant Services Center Drainage and Sewer Review Desk at 684-5362.

The Grading Drainage Plan is the final depiction of the grade changes necessary to install the proposed structural, infrastructure and site improvements. **Erosion control performance standards must be maintained on the site regardless of site disturbance.**

Plot Plan - In addition to the Plot Plan Standards for the Project Type.

Req.	Prov.	
		Show existing and proposed finished grades (elevations) at a 2 foot contour interval
		clearly labeled for proposed structural, infrastructure and site improvements. Indicate quantity of excavation and quantity of fill (in cubic yards) on the cover sheet. Show the surveyed location of all Significant Trees required to be retained within and adjacent to the clearing limits, and give the accurate dimensions of their associated
		drip lines. Show details for tree protection techniques for these Significant Trees to be retained. Show the location of all proposed structures and impervious surfaces (improvements). If these are adjacent to an ECA, show the distance from the
		improvement to the ECA boundary or setback. Show the location of all temporary stockpiles and excavations. Provide cross section showing the maximum slopes and height and/or depth.
		Show temporary shoring methods if used or engineered cut recommended by geotechnical engineer.
		If excavated soil is transported to another site in the City of Seattle limits, provide Grading permit or application number. If location is unknown, provide a letter that this information can be provided prior to excavation.
		For structural fill, specify the following minimum design criteria. Compaction criteria Soil bearing pressure Equivalent fluid pressure Passive pressure Coefficient of friction

Revised 2/24/04 Page 1 of 3

Grading, Drainage & Stormwater
Index 14

Plot Plan - continued

Req.	Prov.	
		If the property line is within a 1:1 slope of the bottom of the excavation, provide one
		of the following:
		A temporary easement or a letter from the owner of the neighboring property
		giving permission to backslope the excavation onto his/her property.
		A report from a geotechnical engineer justifying a temporary slope that will prevent the excavation from encroaching on the neighboring property.
		Design drawings for a temporary shoring system, accompanied by a report
		from a geotechnical engineer stating the design criteria for the shoring.
\boxtimes		Specify immediate and long term use of property
		Identify past industrial or manufacturing uses or hazardous materials, treatment
		disposal or storage that has occurred on the site.
		Show location of existing and planned, temporary and permanent drainage control
		facilities if drainage review required.
		Show the location of existing and proposed drainage discharge point, watercourses,
\bowtie		drainage patterns and are4as of standing water if drainage review required.
	ring l	Show locations of Rockeries and/or other Erosion Control methods. nformation (if shoring proposed)
		Include detailed shoring plans which are prepared by and bear the seal of a
		structural engineer licensed in the State of Washington (if cut is less than 12', Civil
		Engineer okay).
\boxtimes		Identify shoring methods such as (soldier / augur cast piles, sheet piles, soil nai
		systems).
		Dimension location of shoring piles. Dimension clearance to property line.
X		Show diameter of the pile.
		Show piles and their numbering system for each elevation.
		Show all tiebacks. Reference callouts for cross sections and details.
	H	Provide profiles of proposed and existing foundations adjacent to shoring structures
		and/or abutting the public right-of-way.
Elev	otion	
	ation	Views
		Show and label north, south, east and west elevation views of each shoring wall.
X		Show piles for each elevation.
		Show height of the piles.
		Show lagging between piles (if required). Show all tie backs with their elevations.
Ħ	H	Show top and bottom elevations of excavation.
		Show embedded length of piles.
Sho	rina D	Details Control of the control of th
	y D	
		Show pressure diagram. Show tieback connection details

Revised 2/24/04 Page 2 of 3

Grading, Drainage & Stormwater
Index 14

Shoring Details - continued					
Req.	Prov.				
\boxtimes		Show lagging connection details.			
\boxtimes		Show drainage behind the shoring wall.			
\boxtimes		For any work within the right-of-way, a Street Use Permit must be applied for and			
		received prior to approval of a Shoring Permit.			

Structural Notes and Specifications

Provide design parameters and material specifications, including allowable stresses.

Provide engineering recommendations for installation of anchoring systems, including detailed monitoring, testing and inspection programs for all, but not limited to, the following activities:

- 1. Installation of soldier piles.
- 2. Installation and testing of tieback anchors.
- 3. Shoring system displacement and settlement monitoring system.
- 4. Post tensioned or pre-stressing steel; special inspection required during prestressing and grouting operations.
- 5. Concrete placement: Special Inspection Required.
- 6. Structural Welding: Special Inspection Required.
- 7. Geotechnical engineering and surveying information gathered weekly.
- 8. Verification of department and location of utilities, including power, water and sewer prior to anchor drilling.

Show rockery and/or retaining structure locations, height and drainage method.

Revised 2/24/04 Page 3 of 3